





Customer Information Sheet

DRAWING NO.:	SHEET 1 OF 2	IF IN DOUBT - ASK	©	NOT TO SCALE	THIRD ANGLE PROJECTION	ALL DIMENSIONS IN mm
--------------	--------------	-------------------	---	--------------	------------------------	----------------------

- 1.Material: Brass#6801
- 2.M*/Pitch:M2.0*P0.4mm; Rated Current: 20A
- 3.Tightening Torque: $\leq 1.5\text{kgf-cm}$ (14.7N-cm)
- 4.Electroplating: Matte Tin(3-5um) over Nickel
- 5.Recommended Solder Paste Thickness: 0.15mm(150umMin.)
- 6.Service Temperature: -40°C-150°C
- 7.Re-flow Oven Peak Temperature: 245°C-260°C
- 8.Packing Quantity: 800 PCS / reel
- 9.Tolerance : $\pm 0.1\text{mm}$ unless otherwise specified.
- 10.RoHS Compliant & Reach Approval



- Layout Area
- Solder Area
- Through Hole



UT	1	06DEC22	-----
NAME	ISS.	DATE	CN/CO
APPROVED: Walker / Meizy			
CHECKED: Thiri			
DRAWN: UT			

HARWIN

www.harwin.com

TOLERANCES
 X. = $\pm 1\text{mm}$
 X.X = $\pm 0.50\text{mm}$
 X.XX = $\pm 0.20\text{mm}$
 X.XXX = $\pm 0.01\text{mm}$
 ANGLES = $\pm 5^\circ$
 UNLESS STATED

THIS DRAWING AND ANY INFORMATION OR
 DESCRIPTIVE MATTER SET OUT HEREON ARE
 CONFIDENTIAL AND COPYRIGHT PROPERTY OF
 THE HARWIN GROUP AND MUST NOT BE
 DISCLOSED, LOANED, COPIED OR USED FOR
 MANUFACTURING, TENDERING OR FOR ANY
 OTHER PURPOSE WITHOUT THEIR WRITTEN
 PERMISSION.

MATERIAL & FINISH:

SEE ABOVE

TITLE:

EMI/ESD/RFI SMT Nut;BOSS;Stand_off

DRAWING NUMBER:

MMS-B40M20D314416T


SHT
 1
 OF 2

Customer Information Sheet



DRAWING NO.: SHEET 2 OF 2 IF IN DOUBT - ASK © NOT TO SCALE THIRD ANGLE PROJECTION ALL DIMENSIONS IN mm

t	P2	P0	D1	D	E	F	P1	Ko	Bo	Ao	W	ITEM
0.5±0.05	2.00±0.1	4.00±0.1	0.00±0.1	1.50±0.1	1.75±0.1	7.50±0.1	12.0±0.1	6.65±0.1	4.24±0.1	4.24±0.1	16.0±0.3	SPEC

ITEM	SPEC
W	16.00 ^{+0.30} _{-0.30}
Ao	4.24 ^{+0.10} _{-0.10}
Bo	4.24 ^{+0.10} _{-0.10}
Ko	6.65 ^{+0.10} _{-0.10}
P	12.00 ^{+0.10} _{-0.10}
F	7.50 ^{+0.10} _{-0.10}
E	1.75 ^{+0.10} _{-0.10}
D	1.50 ^{+0.10} _{-0.00}
D1	0.00 ^{+0.10} _{-0.10}
Po	4.00 ^{+0.10} _{-0.10}
P2	2.00 ^{+0.10} _{-0.10}
t	0.50 ^{+0.05} _{-0.05}



REEL DIMENSIONS



UT	1	8OCT12	-----
NAME	ISS.	DATE	CN/CO
APPROVED: Walker / Meizy			
CHECKED: Thiri			
DRAWN: UT			

HARWIN

www.harwin.com

TOLERANCES
X. = ±1mm
X.X = ±0.50mm
X.XX = ±0.20mm
X.XXX = ±0.01mm
ANGLES = ±5°
UNLESS STATED

THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE MATTER SET OUT HEREON ARE CONFIDENTIAL AND COPYRIGHT PROPERTY OF THE HARWIN GROUP AND MUST NOT BE DISCLOSED, LOANED, COPIED OR USED FOR MANUFACTURING, TENDERING OR FOR ANY OTHER PURPOSE WITHOUT THEIR WRITTEN PERMISSION.

MATERIAL & FINISH:

PACKAGE QUANTITY

800 PCS / REEL

TITLE:

EMI/ESD/RFI SMT Nut;BOSS; Stand_off

DRAWING NUMBER:

MMS-B40M20D314416T

SHT
2
OF 2